

Indicating Valves, Butterfly or Ball Type

Design features provide a dependable visible indication of the open position even at a distance. If excessive force is applied to the handle, weakness-joints will break so as to preserve correct orientation between indicator and valve position. Valve and indicator parts are so designed that they can be assembled only one way, always to give correct indication. All FM Approved indicating valves turn clockwise to shut. They are small, lightweight, and, because of a resilient seat, are easy to operate. They are not subject to sticking or dropped gates. They are not recommended for throttling service. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Models F1022-300, 300psi, F0811-300, 300psi

Model Number	Product Type	Nominal Pipe Size, inch (mm)	Rated Working Pressure, psi (kPa)	Remarks
F1022-300	Butterfly Valve, Grooved Ends	2, 2-1/2, 3, 4, 5, 6 (50, 65, 80, 100, 125, 150)	300 (2070)	a, b, c
F0811-300	Butterfly Valve, Wafer Style	2, 2-1/2, 3, 4, 5, 6 (50, 65, 80, 100, 125, 150)	300 (2070)	a, b, c

Remarks:

- a. Available with dual supervisory switches.
- b. FM Approved for indoor and outdoor service.
- c. FM Approved for aboveground installations only.

Company Name:	Weflo Valve Co., Ltd
Company Address:	Intersection of Huadong Road and Chunyang Road, National High-Tech Industrial Development Zone, Qingdao, P.R. China 266111
Company Website:	http://www.weflovalve.com
New/Updated Product Listing:	No
Listing Country:	China
Certification Type:	FM Approved