

Single Check Valves

Single check valves are used in fire protection systems to allow waterflow in one direction only. Typical applications are at connections between public water supplies and private fire service systems, at the discharge from fire pumps, at gravity tank connections and at fire service pumper connections.

Valves identified in the listing by a single asterisk (*) have side covers; valves identified by a double asterisk (**) have no removable covers; others have top covers. Clearance must be provided for side-cover valves to permit clapper removal. Valves without covers must be removed from the system for clapper replacement or repair. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Fig No. F0311-300, F0311-250, F0311-200, Fig No. F0322-300, F0322-250, F0322-200

Model No.	Description	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
Fig. F0311-300	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	300 (2070)	a
Fig. F0311-250	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	250 (1725)	a
Fig. F0311-200	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	200 (1380)	a
Fig No. F0322-300	Swing Check Valve, Grooved Ends	2, 2 1/2, 76.1 mm, 3, 4, 5, 6, 8, 10, 12	300 (2070)	a
Fig No. F0322-250	Swing Check Valve, Grooved Ends	2, 2 1/2, 76.1 mm, 3, 4, 5, 6, 8, 10, 12	250 (1725)	a
Fig No. F0322-200	Swing Check Valve, Grooved Ends	2, 2 1/2, 76.1 mm, 3, 4, 5, 6, 8, 10, 12	200 (1380)	a

Remarks:

a. Resilient Seat

Company Name:	Weflo Valve Co., Ltd
Company Address:	Intersection of Huadong Road and Chunyang Road, National High-Tech Industrial Development Zone, Qingdao, P.R. China 266111
Company Website:	http://www.weflovalve.com
New/Updated Product Listing:	No
Listing Country:	China
Certification Type:	FM Approved