

HMER.EX15264 Check Valves

Page Bottom

Check Valves

See General Information for Check Valves

WEFLO VALVE CO LTD EX15264

Intersection of Huadong Rd and Chunyang Rd Qingdao National High-tech Industrial Development Zone QINGDAO, SHANDONG 266111 CHINA

Swing type, Model F0411-175, 4, 6, 8, 10 and 12 size wafer style check values rated working pressure of 175 psig (1210 Kpa) vertical installation.

Model F0311-300, sizes 2, 2-1/2, 3, 4, 5, 6, 8, 10 and 12 in. (50.8, 63.5, 76.2, 101.6, 127, 139.7, 203.2, 254 and 304.8 mm), with rubber faced checks for working pressures not exceeding 300, 250 and 200 psig (2068, 1724 and 1379 Kpa). Installation - horizontal or vertical.

Model F0322-300, sizes 2, 2-1/2, 3, 4, 5, 6, 8, 10 and 12 in. (63.5, 76.2, 101.6, 127, 139.7, 203.2, 254 and 304.8 mm), with rubber faced checks for working pressures not exceeding 300, 250 and 200 psig (2068, 1724 and 1379 Kpa). Installation – horizontal or vertical.

Model F0322-300, sizes 2, 2-1/2, 3, 4 in., threaded by grooved end configuration, with rubber faced checks for working pressures not exceeding 300 psig, 250 and 200 (2068, 1724 and 1379 Kpa). Installation - horizontal or vertical.



Trademark and/or Tradename:

Last Updated on 2016-09-14

Questions? Print this page Terms of Use Page Top

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a nonmisleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".